

~~CONFIDENTIAL~~

NACA RM L53108a

8.2



# RESEARCH MEMORANDUM

EXAMINATION OF RECENT LATERAL-STABILITY-DERIVATIVE DATA

By Frank S. Malvestuto, Jr., and Richard E. Kuhn

Langley Aeronautical Laboratory  
Langley Field, Va.

CLASSIFICATION CHANGED

**UNCLASSIFIED**

By authority of *NASA memorandum dated July 17, 1963,*  
*S/P. M. Lovell, Jr.*

CLASSIFIED DOCUMENT

*HSR-8-5-63*

This material contains information affecting the National Defense of the United States within the meaning of the espionage laws, Title 18, U.S.C., Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

## NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WASHINGTON  
October 22, 1953

~~CONFIDENTIAL~~



## NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

## RESEARCH MEMORANDUM

## EXAMINATION OF RECENT LATERAL-STABILITY-DERIVATIVE DATA

By Frank S. Malvestuto, Jr., and Richard E. Kuhn

## INTRODUCTION

In the present paper attention is directed to the aerodynamic parameters, the so-called stability derivatives, that affect the lateral behavior of airplanes and missiles. The discussion is centered on three important quantities  $C_{l\beta}$ , the effective-dihedral derivative,  $C_{n\beta}$ , the directional-stability derivative, and  $C_{lp}$ , the damping-in-roll derivative. These quantities are considered for a large angle-of-attack range at subsonic speeds. A few remarks will also be made on the sideslip derivatives at zero lift in the supersonic speed range.

## DISCUSSION

For the subsonic speed range, the lateral-stability derivatives have been the subject of intensive research by the Langley high-speed 7- by 10-foot tunnel. Particular attention has been paid to the variation with Mach number in the high angle-of-attack range that is representative of flyable attitudes of many high-speed airplanes. The effective-dihedral and the directional-stability derivatives of the three complete models sketched in figure 1 are presented in figures 2 and 3. Model I is equipped with a  $30^\circ$  sweptback wing of aspect ratio 3; model II has a  $45^\circ$  swept wing of aspect ratio 4; and model III (representing the X-5 airplane) is equipped with a  $60^\circ$  swept wing of aspect ratio 2. To the right of each sketch in figure 1 is a plot of the model lift coefficient against angle of attack for two available Mach numbers indicative of the low and high subsonic speed range.

The effective-dihedral derivative  $C_{l\beta}$ , expressed here in radians, for the three models is presented in figure 2 for the range of angle of attack and the Mach numbers indicated in figure 1. It is important to note the highly nonlinear variation of this derivative with angle of attack and the pronounced effect of Mach number on these variations. This nonlinear behavior is strongly dependent upon the separation of flow from the wings, particularly in the vicinity of the tips, and

commences at angles of attack at which these swept wings are by no means completely stalled. Note that model I retains its positive effective dihedral (that is,  $-C_{l\beta}$ ) through the angle-of-attack range and increasing Mach number tended to increase this quantity at the higher angles. Models II and III have the more typical variation of  $C_{l\beta}$  with angle of attack and show the decrease to zero and to negative effective dihedral at the higher angles. Configurations having this latter type of variation of  $C_{l\beta}$  and the derivative  $C_{n\beta}$ , to be discussed later, could easily be flying at angles at which one or the other of these derivatives becomes zero. These zero values of the derivatives could seriously affect the lateral behavior of airplanes at these higher angles of attack. The point to be observed from the data presented here is that increasing Mach number may change the angle of attack at which these derivatives become zero. As an illustration, the results of model II show that increasing Mach number increases the angle at which  $C_{l\beta}$  and  $C_{n\beta}$  become zero; whereas, for model III, the Mach number effect is reversed; that is, increasing Mach number decreases the angle of attack at which zero values occur.

The effects of angle of attack and Mach number on the companion derivative  $C_{n\beta}$  are shown in figure 3. At the higher angles the variation of this derivative depends not only upon the tail effectiveness, that is, the difference between the tail-on and tail-off results, but also may be greatly influenced by the variation of the wing-body characteristics. As an example, for models I and II the increase in the stability of the wing-body combination at the higher Mach number tends to compensate for the reduction in tail effectiveness shown by the decrease in the increment between the tail-on and tail-off results. For model III, however, although the tail effectiveness remains appreciably constant up to large angles of attack, the decrease in the stability of the wing-body combination causes a reduction in  $C_{n\beta}$  for the complete model and is the primary cause of this reduction. It is also of interest to point out for this model that the angle of attack at which  $C_{l\beta}$  and  $C_{n\beta}$  tend to zero is approximately the same and decreases with increasing Mach number. This similarity of the action of Mach number on  $C_{l\beta}$  and  $C_{n\beta}$  is not surprising since for this model the wing-body characteristics, which in the main usually control  $C_{l\beta}$ , are also the controlling influence for  $C_{n\beta}$  as was indicated previously. These results emphasize the need for having, through the Mach range, not only proper tail effectiveness, but equally important, proper wing-body design, incorporating satisfactory directional characteristics.

The effects of horizontal-tail height on the directional-stability derivative  $C_{n\beta}$  and also on the effective-dihedral derivative  $C_{l\beta}$  for model I are shown in figures 4 and 5. The curves on the left of each figure represent horizontal-tail-off data; the next set of curves are for the horizontal tail in the low position. This arrangement is the one considered in the previous figures. The data to the right are for the horizontal tail in high position. The expected increase in the directional-stability derivative with the tail in the high position is clearly evident from these results. For the effective-dihedral derivative  $C_{l\beta}$ , the relocation of the tail from the low to the high position produced again, as expected, an increase in the negative value of the derivative.

There is one additional point related to the sideslip derivatives that deserves consideration. In attempts to devise "optimum fixes" to alleviate the pitch-up conditions for various airplanes, consideration has also been given to the effect of these same fixes on the lateral derivatives. The results available so far are very limited and no specific conclusion can be made. The data of figure 6, however, illustrate for one configuration, model III, the effect of a leading-edge chord-extension on the  $C_{n\beta}$  and  $C_{l\beta}$  derivatives. At the lower Mach number the effect of chord-extensions in producing a linear pitching-moment variation is clearly evident, but the effect of these chord-extensions on the corresponding  $C_{n\beta}$  and  $C_{l\beta}$  derivatives are relatively insignificant. At the higher Mach number, although unfortunately the available chord-extension-on data are somewhat incomplete, the small effect of these chord-extensions on the derivatives is still evident, the trend for the higher Mach number being almost identical to that shown for the lower Mach number. It should be remembered, of course, that  $C_{l\beta}$  did not show any pronounced breaks until angles of attack approaching stall were reached.

So far, the discussion of the lateral derivatives for the subsonic speed range has been directed toward the static effects. Recently, the characteristics in steady roll of several wings at high angles of attack in the subsonic speed range have been investigated experimentally. For a  $45^\circ$  swept-wing-body arrangement, the variation of the damping-in-roll parameter  $C_{lp}$  with angle of attack and Mach number is shown in figure 7,

together with the corresponding lift variations. It can be seen that at a Mach number of 0.2 the wing maintains a reasonable amount of damping at all angles of attack up to the stall. However, as the Mach number is increased, the damping-in-roll ability of the wing seriously diminishes until at a Mach number of 0.91 instability in roll is indicated at an angle of attack of  $11^\circ$ . Note also that this effect occurs although the lift is still increasing at this angle of attack. Similar effects occur

for wings of other plan forms as indicated in figure 8. It will be noted here that all these wings indicate a serious loss in damping effectiveness in about the same angle-of-attack range. Note also that, with the exception of the unswept wing, this loss occurs although the over-all lift coefficients of the wings are still increasing. For the unswept wing, this loss in damping occurs at angles of attack corresponding to the stall, as would be expected.

One additional important point connected with these regions of poor damping is that the variation of rolling moment with rolling velocity may be very irregular as shown in figure 9. Under these conditions it is difficult to determine a representative value of the damping coefficient. The data shown in figure 9 are for a Mach number of 0.85. The variation of the rolling-moment coefficient with rolling velocity shown by the dashed curve is representative of the linear stable slope characteristic of the low angle-of-attack range. At an angle of attack of  $11^\circ$ , however, the variation is nonlinear and, in the case of the  $32.6^\circ$  swept wing, it is unstable over a very wide range of  $pb/2V$ . The hysteresis shown in the data for the unswept wing and the  $60^\circ$  triangular wing would certainly give rise to some undesirable dynamic-stability characteristics and possibly complicate the design of any automatic stabilizing equipment. The instability at small values of  $pb/2V$  and the associated hysteresis loops also may have some relationship to the wing-dropping problem.

Some consideration has been given to the use of fences in an attempt to reduce the loss of damping in roll. Since a loss in damping is associated with tip stalling, which is also a contributing factor in producing pitch-up, tests were made to determine whether devices which are known to alleviate pitch-up would also improve the damping in roll. The effect of a fence on the damping characteristics of the  $45^\circ$  swept wing is shown in figure 10. The fences were full chord and were located at the  $0.65 b/2$  station. For the Mach number of 0.85, the fences delayed the pitch-up by some  $5^\circ$  and decidedly improved the damping. At a Mach number of 0.91, however, the effect of the fences on either the damping or the pitch-up decreased considerably. Reference 1 contains a more complete discussion of the damping-in-roll characteristics of swept wings at high angles of attack and high subsonic speeds. Included also in this report is a simple procedure for estimating the load distribution in roll provided the corresponding angle-of-attack load distribution is known.

The preceding discussion of the lateral-stability derivatives at high angles of attack has of necessity been based wholly on experimental data. This discussion has been confined to the subsonic speed range. In the supersonic speed range, recent theoretical work applied to three complete configurations has demonstrated the ability of theory to predict the lateral-stability derivatives at low angles of attack. The variations of the derivatives  $C_{l_\beta}$  and  $C_{n_\beta}$  with Mach number for these three

configurations are shown in figures 11 and 12. The theoretical results are presented for the complete arrangement, vertical-tail alone, and body or wing-body alone. The experimental results, the dark circles, are for the complete arrangement. The comparison of theory and experiment indicates that the level and trend of the experimental variations are predicted by the theory. For one of these airplanes a thorough study and prediction of all the major longitudinal and lateral derivatives has been made and is reported in reference 2.

#### CONCLUDING REMARKS

It has not been possible to consider all the recent information on lateral-stability derivatives. However, a bibliography of papers containing lateral-stability-derivative data has been attached. Reference 3 also contains a large number of references not included here. The following remarks are offered as an indication of the present general status of the stability-derivative field.

At low angles of attack within the subsonic speed range below the critical Mach number, it is felt that available theory permits fairly reliable predictions of the lateral-stability derivatives.

At the higher angles of attack in the subsonic and transonic ranges, the unpredictable, nonlinear characteristics of the derivatives stress the necessity for determining experimentally for a particular configuration the derivatives needed in the estimation of stability.

In the supersonic range at low angles of attack, combined theoretical and experimental studies have produced useful aerodynamic-derivative data. For the complete configurations so far considered, derivative estimates\* made for these conditions have met with a good measure of success.

In the supersonic range at high angles of attack there are no data available.

Langley Aeronautical Laboratory,  
National Advisory Committee for Aeronautics,  
Langley Field, Va., August 26, 1953.

REFERENCES

1. Kuhn, Richard E.: Notes on Damping in Roll and Load Distributions in Roll at High Angles of Attack and High Subsonic Speed. NACA RM L53G13a, 1953.
2. Margolis, Kenneth, and Bobbitt, Percy J.: Theoretical Calculations of the Stability Derivatives at Supersonic Speeds for a High-Speed Airplane Configuration. NACA RM L53G17, 1953
3. Campbell, John P., and McKinney, Marion O.: Summary of Methods for Calculating Dynamic Lateral Stability and Response and for Estimating Lateral Stability Derivatives. NACA Rep. 1098, 1952. (Supersedes NACA TN 2409.)

BIBLIOGRAPHY

## THEORETICAL STUDIES AND ESTIMATING PROCEDURES

4. Purser, Paul E.: An Approximation to the Effect of Geometric Dihedral on the Rolling Moment Due to Sideslip for Wings at Transonic and Supersonic Speeds. NACA RM L52B01, 1952.
5. Margolis, Kenneth, Sherman, Windsor L., and Hannah, Margery E.: Theoretical Calculation of the Pressure Distribution, Span Loading, and Rolling Moment Due to Sideslip at Supersonic Speeds for Thin Sweptback Tapered Wings With Supersonic Trailing Edges and Wing Tips Parallel to the Axis of Wing Symmetry. NACA TN 2898, 1953.
6. Robinson, A., and Hunter-Tod, J. H.: The Aerodynamic Derivatives With Respect to Sideslip for a Delta Wing With Small Dihedral at Supersonic Speeds. Rep. No. 12, College of Aero., Cranfield (British), Dec. 1947.
7. Nonweiler, T.: Theoretical Stability Derivatives of a Highly Swept Delta Wing and Slender Body Combination. Rep. No. 50, College of Aero., Cranfield (British), Nov. 1951.
8. Jacobs, Willi: Lift and Moment Changes Due to the Fuselage for a Yawed Aeroplane With Unswept and Swept Wings. Rep. No. 34, Aero. Res. Inst. of Sweden (Stockholm), 1950.
9. Ksoll, R.: Theoretical Investigations on the Rolling Moment Due to Side Slip of Wing and Fuselage Arrangements With a Fuselage of Pear Shaped Cross Section. Repts. and Translations No. 134, British M.O.S.(A) Völkenrode, Aug. 1946.

10. Martin, John C., and Malvestuto, Frank S., Jr.: Theoretical Force and Moments Due to Sideslip of a Number of Vertical Tail Configurations at Supersonic Speeds. NACA TN 2412, 1951.
11. Riley, Donald R.: Effect of Horizontal-Tail Span and Vertical Location on the Aerodynamic Characteristics of an Unswept Tail Assembly in Sideslip. NACA TN 2907, 1953.
12. Coale, Charles W.: Restoring Moment in Yaw Due to Interference Between the Vertical Stabilizer and Fuselage at Supersonic Velocities. Rep. No. SM-13496, Douglas Aircraft Co., Inc., Feb. 7, 1949.
13. Owen, P. R., and Andersen, R. G.: Interference Between the Wings and the Tail Surfaces of a Combination of Slender Body, Cruciform Wings and Cruciform Tail Set at Both Incidence and Yaw. Rep. No. Aero. 2471, British R.A.E., June 1952.
14. Tscherfing, W., and Decker, J. L.: Directional Stability Characteristics of Tee-Tails. Eng. Rep. No. 4797, The Glenn L. Martin Co., Feb. 20, 1952.
15. Falkner, V. M.: Rotary Derivatives in Yaw. Aircraft Engineering, vol. XXIII, no. 264, Feb. 1951, pp. 44-50, 54.
16. Hunter-Tod, J. H.: The Aerodynamic Derivatives With Respect to Rate of Yaw for a Delta Wing With Small Dihedral at Supersonic Speeds. Rep. No. 28, College of Aero., Cranfield (British), March 1949.
17. Ribner, Herbert S.: On the Effect of Subsonic Trailing Edges on Damping in Roll and Pitch of Thin Sweptback Wings in a Supersonic Stream. NACA TN 2146, 1950.
18. Ribner, Herbert S.: Damping in Roll of Cruciform and Some Related Delta Wings at Supersonic Speeds. NACA TN 2285, 1951.
19. Martina, Albert P.: Method for Calculating the Rolling and Yawing Moments Due to Rolling for Unswept Wings With or Without Flaps or Ailerons by Use of Nonlinear Section Lift Data. NACA TN 2937, 1953.
20. Diederich, Franklin W.: A Simple Approximate Method for Calculating Spanwise Lift Distributions and Aerodynamic Influence Coefficients at Subsonic Speeds. NACA TN 2751, 1952.
21. Diederich, Franklin W., and Zlotnick, Martin: Theoretical Spanwise Lift Distributions of Low-Aspect-Ratio Wings at Speeds Below and Above the Speed of Sound. NACA TN 1973, 1949.

22. Diederich, Franklin W.: A Plan-Form Parameter for Correlating Certain Aerodynamic Characteristics of Swept Wings. NACA TN 2335, 1951.
23. DeYoung, John: Theoretical Antisymmetric Span Loading for Wings of Arbitrary Plan Form at Subsonic Speeds. NACA Rep. 1056, 1951. (Supersedes NACA TN 2140.)
24. Moeckel, W. E., and Evvard, J. C.: Load Distributions Due to Steady Roll and Pitch for Thin Wings at Supersonic Speeds. NACA TN 1689, 1948.
25. Bleviss, Zegmund O.: Some Roll Characteristics of Cruciform Delta Wings at Supersonic Speeds. Jour. Aero. Sci., vol. 18, no. 5, May 1951, pp. 289-297.
26. Bleviss, Zegmund O.: Some Roll Characteristics of Plane and Cruciform Delta Ailerons and Wings in Supersonic Flow. Rep. No. SM-13431, Douglas Aircraft Co., Inc., June 1949.
27. Lagerstrom, P. A., and Graham, Martha E.: Some Aerodynamic Formulas in Linearized Supersonic Theory for Damping in Roll and Effect of Twist for Trapezoidal Wings. Rep. No. SM-13200, Douglas Aircraft Co., Inc., March 12, 1948.
28. Graham, Ernest W.: A Limiting Case for Missile Rolling Moments. Jour. Aero. Sci., vol. 18, no. 9, Sept. 1951, pp. 624-628.
29. Miles, John W.: A Note on the Damping in Roll of a Cruciform Winged Body. Quarterly Appl. Math., vol. X, no. 3, Oct. 1952, pp. 276-277.
30. Adams, Gaynor J., and Dugan, Duane W.: Theoretical Damping in Roll and Rolling Moment Due to Differential Wing Incidence for Slender Cruciform Wings and Wing-Body Combinations. NACA Rep. 1088, 1952.
31. Van Meter, J. T.: Damping in Roll of Triangular Planform Wings in Supersonic Flow. Meteor Rep. UAC-34, United Aircraft Corp., June 1949.
32. Lehrian, Doris E.: Calculation of the Damping for Rolling Oscillations of a Swept Wing. C. P. No. 51, British N.P.L. (Tech. Rep. 13,448, A.R.C.), 1951.
33. Bobbitt, Percy J., and Malvestuto, Frank S., Jr.: Estimation of Forces and Moments Due to Rolling for Several Slender-Tail Configurations at Supersonic Speeds. NACA TN 2955, 1953.
34. Martin, John C., and Gerber, Nathan: On the Effect of Thickness on the Damping in Roll of Airfoils at Supersonic Speeds. Rep. No. 843, Ballistic Res. Labs., Aberdeen Proving Ground, Jan. 1953.

35. Nicolaidis, John D., and Bolz, Ray E.: On the Pure Rolling Motion of Winged and/or Finned Missiles in Varying Supersonic Flight. Rep. No. 799, Ballistic Res. Labs., Aberdeen Proving Ground, March 1952.
36. Steinmetz, Harold F.: Wing-Body Interference Effects on the Tail Contribution to the Damping-in-Roll of Supersonic Missiles. Preprint No. 384, S.M.F. Fund Paper, Inst. Aero. Sci.

## EXPERIMENTAL STUDIES

## Wing and Wing-Fuselage Data

37. Letko, William, and Wolhart, Walter D.: Effect of Sweepback on the Low-Speed Static and Rolling Stability Derivatives of Thin Tapered Wings of Aspect Ratio 4. NACA RM L9F14, 1949.
38. Brewer, Jack D., and Fisher, Lewis R.: Effect of Taper Ratio on the Low-Speed Rolling Stability Derivatives of Swept and Unswept Wings of Aspect Ratio 2.61. NACA TN 2555, 1951. (Supersedes NACA RM L8H18.)
39. Letko, William, and Jaquet, Byron M.: Effect of Airfoil Profile of Symmetrical Sections on the Low-Speed Static-Stability and Yawing Derivatives of  $45^\circ$  Sweptback Wing Models of Aspect Ratio 2.61. NACA RM L8H10, 1948.
40. Jaquet, Byron M., and Brewer, Jack D.: Low-Speed Static-Stability and Rolling Characteristics of Low-Aspect-Ratio Wings of Triangular and Modified Triangular Plan Forms. NACA RM L8L29, 1949.
41. Neumark, S.: Lateral Characteristics of Wings of Small Aspect Ratio From Some German Model Tests. Tech. Note No. Aero. 1917, British R.A.E., Sept. 1947.
42. Wolhart, Walter D.: Wind-Tunnel Investigation at Low Speed of the Effects of Symmetrical Deflection of Half-Delta Tip Controls on the Damping in Roll and Yawing Moment Due to Rolling of a Triangular-Wing Model. NACA RM L51B09, 1951.
43. Lichtenstein, Jacob H.: Effect of High-Lift Devices on the Low-Speed Static Lateral and Yawing Stability Characteristics of an Untapered  $45^\circ$  Sweptback Wing. NACA TN 2689, 1952. (Supersedes NACA RM L8G20.)
44. Lichtenstein, Jacob H., and Williams, James L.: Effect of High-Lift Devices on the Static-Lateral-Stability Derivatives of a  $45^\circ$  Sweptback Wing of Aspect Ratio 4.0 and Taper Ratio 0.6 in Combination With a Body. NACA TN 2819, 1952.

45. Fisher, Lewis R.: Low-Speed Static Longitudinal and Lateral Stability Characteristics of Two Low-Aspect-Ratio Wings Cambered and Twisted To Provide a Uniform Load at a Supersonic Flight Condition. NACA RM L51C20, 1951.
46. Salmi, Reino J., and Fitzpatrick, James E.: Yaw Characteristics and Side-wash Angles of a  $42^\circ$  Sweptback Circular-Arc Wing With a Fuselage and With Leading-Edge and Split Flaps at a Reynolds Number of 5,300,000. NACA RM L7I30, 1947.
47. Salmi, Reino J.: Yaw Characteristics of a  $52^\circ$  Sweptback Wing of NACA  $64_1$ -112 Section With a Fuselage and With Leading-Edge and Split Flaps at Reynolds Numbers From  $1.93 \times 10^6$  to  $6.00 \times 10^6$ . NACA RM L8H12, 1948.
48. McCormack, Gerald M., and Walling, Walter C.: Aerodynamic Study of a Wing-Fuselage Combination Employing a Wing Swept Back  $63^\circ$ . Investigation of a Large-Scale Model at Low Speed. NACA RM A8D02, 1949.
49. Hunton, Lynn W., and Dew, Joseph K.: Measurements of the Damping in Roll of Large-Scale Swept-Forward and Swept-Back Wings. NACA RM A7D11, 1947.
50. Cole, Henry A., Jr., and Ganzer, Victor M.: Experimental Investigation of Rolling Performance of Straight and Sweptback Flexible Wings With Various Ailerons. NACA TN 2563, 1951.
51. Adler, Alfred A.: A Correlation of Theory With Experiment for Low-Aspect-Ratio Wings at Subsonic Speeds. Rep. No. AF-743-A-4 (Air Res. and Dev. Command Contract No. AF 33(038)-17397 E.O. No. 460-31-12-12 SR 1g), Cornell Aero. Lab., Inc., Dec. 1952.
52. Thiel, G.: Rolling Balance Measurements. Part II - Results of Tests on Two Tapered Wings. British Ministry of Supply Translation No. GDC 10/451(11)T (R.A.E. Library Trans. 379, pt. 2), Sept. 1951.
53. Halliday, A. S., Cox, D. K., and Skelton, W. C.: Measurement of Rolling Moment on an Elliptic Wing on the N.P.L. Whirling Arm. Rep. 10,935, British A.R.C. (S. & C. 2161), Oct. 16, 1947.
54. Halliday, A. S., and Cox, D. K.: The Measurement of Yawing Moment on an Elliptic Wing on the Whirling Arm. Rep. 12,497, British A.R.C. (S. & C. 2320), Aug. 2, 1949.
55. Kuhn, Richard E., and Fournier, Paul G.: Wind-Tunnel Investigation of the Static Lateral Stability Characteristics of Wing-Fuselage Combinations at High Subsonic Speeds. Sweep Series. NACA RM L52G11a, 1952.

56. Fournier, Paul G., and Byrnes, Andrew L., Jr.: Wind-Tunnel Investigation of the Static Lateral Stability Characteristics of Wing-Fuselage Combinations at High Subsonic Speeds. Aspect-Ratio Series. NACA RM L52L18, 1953.
57. Wiggins, James W., and Fournier, Paul G.: Wind-Tunnel Investigation of the Static Lateral Stability Characteristics of Wing-Fuselage Combinations at High Subsonic Speeds. Taper-Ratio Series. NACA RM L53B25a, 1953.
58. Wiggins, James W.: Wind-Tunnel Investigation at High Subsonic Speeds of the Static-Longitudinal and Static-Lateral Stability Characteristics of a Wing-Fuselage Combination Having a Triangular Wing of Aspect Ratio 2.31 and an NACA 65A003 Airfoil. NACA RM L53G09a, 1953.
59. Fournier, Paul G.: Wind-Tunnel Investigation of the Aerodynamic Characteristics in Pitch and Sideslip at High Subsonic Speeds of a Wing-Fuselage Combination Having a Triangular Wing of Aspect Ratio 4. NACA RM L53G14a, 1953.
60. Kuhn, Richard E., and Draper, John W.: Wind-Tunnel Investigation of the Effects of Geometric Dihedral on the Aerodynamic Characteristics in Pitch and Sideslip of an Unswept- and a  $45^\circ$  Sweptback-Wing-Fuselage Combination at High Subsonic Speeds. NACA RM L53F09, 1953.
61. Johnson, Harold S.: Wind-Tunnel Investigation at Low Transonic Speeds of the Effects of Number of Wings on the Lateral-Control Effectiveness of an RM-5 Test Vehicle. NACA RM L9H16, 1949.
62. Lockwood, Vernard E.: Damping-in-Roll Characteristics of a  $42.7^\circ$  Sweptback Wing As Determined From a Wind-Tunnel Investigation of a Twisted Semispan Wing. NACA RM L9F15, 1949.
63. Lockwood, Vernard E.: Effects of Sweep on the Damping-in-Roll Characteristics of Three Sweptback Wings Having an Aspect Ratio of 4 at Transonic Speeds. NACA RM L50J19, 1950.
64. Kuhn, Richard E., and Myers, Boyd C., II: The Effect of Tip Tanks on the Rolling Characteristics at High Subsonic Mach Numbers of a Wing Having an Aspect Ratio of 3 With Quarter-Chord Line Swept Back  $35^\circ$ . NACA RM L9J19, 1950.
65. Myers, Boyd C., II, and Kuhn, Richard E.: High-Subsonic Damping-in-Roll Characteristics of a Wing With the Quarter-Chord Line Swept Back  $35^\circ$  and With Aspect Ratio 3 and Taper Ratio 0.6. NACA RM L9C23, 1949.
66. Kuhn, Richard E., and Myers, Boyd C., II: Effects of Mach Number and Sweep on the Damping-in-Roll Characteristics of Wings of Aspect Ratio 4. NACA RM L9E10, 1949.

67. Stone, David G.: A Collection of Data for Zero-Lift Damping in Roll of Wing-Body Combinations As Determined With Rocket-Powered Models Equipped With Roll-Torque Nozzles. NACA RM L53E26, 1953.
68. Bland, William M., Jr., and Dietz, Albert E.: Some Effects of Fuselage Interference, Wing Interference, and Sweepback on the Damping in Roll of Untapered Wings As Determined by Techniques Employing Rocket-Propelled Vehicles. NACA RM L51D25, 1951.
69. Sanders, E. Claude, Jr., and Edmondson, James L.: Damping in Roll of Rocket-Powered Test Vehicles Having Swept, Tapered Wings of Low Aspect Ratio. NACA RM L51G06, 1951.
70. Sanders, E. Claude, Jr.: Damping in Roll of Straight and  $45^\circ$  Swept Wings of Various Taper Ratios Determined at High Subsonic, Transonic, and Supersonic Speeds With Rocket-Powered Models. NACA RM L51H14, 1951.
71. Sanders, E. Claude, Jr.: Damping in Roll of Models With  $45^\circ$ ,  $60^\circ$ , and  $70^\circ$  Delta Wings Determined at High Subsonic, Transonic, and Supersonic Speeds With Rocket-Powered Models. NACA RM L52D22a, 1952.
72. Edmondson, James L.: Damping in Roll of Rectangular Wings of Several Aspect Ratios and NACA 65A-Series Airfoil Sections of Several Thickness Ratios at Transonic and Supersonic Speeds As Determined With Rocket-Powered Models. NACA RM L50E26, 1950.
73. Stone, David G., and Sandahl, Carl A.: A Comparison of Two Techniques Utilizing Rocket-Propelled Vehicles for the Determination of the Damping-in-Roll Derivative. NACA RM L51A16, 1951.
74. Edmondson, James L., and Sanders, E. Claude, Jr.: A Free-Flight Technique for Measuring Damping in Roll by Use of Rocket-Powered Models and Some Initial Results for Rectangular Wings. NACA RM L9I01, 1949.
75. Dietz, Albert E., and Edmondson, James L.: The Damping in Roll of Rocket-Powered Test Vehicles Having Rectangular Wings With NACA 65-006 and Symmetrical Double-Wedge Airfoil Sections of Aspect Ratio 4.5. NACA RM L50B10, 1950.
76. Bland, William M., Jr., and Sandahl, Carl A.: A Technique Utilizing Rocket-Propelled Test Vehicles for the Measurement of the Damping in Roll of Sting-Mounted Models and Some Initial Results for Delta and Unswept Tapered Wings. NACA RM L50D24, 1950.
77. Hopko, Russell N.: A Flight Investigation of the Damping in Roll and Rolling Effectiveness Including Aeroelastic Effects of Rocket-Propelled Missile Models Having Cruciform, Triangular, Interdigitated Wings and Tails. NACA RM L51D16, 1951.

78. Strass, H. Kurt, and Marley, Edward T.: Rolling Effectiveness of All-Movable Wings at Small Angles of Incidence at Mach Numbers From 0.6 to 1.6. NACA RM L51H03, 1951.
79. Bland, William M., Jr.: Effect of Fuselage Interference on the Damping in Roll of Delta Wings of Aspect Ratio 4 in the Mach Number Range Between 0.6 and 1.6 As Determined With Rocket-Propelled Vehicles. NACA RM L52E13, 1952.
80. Martz, C. William, and Church, James D.: Flight Investigation at Subsonic, Transonic, and Supersonic Velocities of the Hinge-Moment Characteristics, Lateral-Control Effectiveness, and Wing Damping in Roll of a 60° Sweptback Delta Wing With Half-Delta Tip Ailerons. NACA RM L51G18, 1951.
81. Brown, Clinton E., and Heinke, Harry S., Jr.: Preliminary Wind-Tunnel Tests of Triangular and Rectangular Wings in Steady Roll at Mach Numbers of 1.62 and 1.92. NACA RM L8L30, 1949.
82. McDearmon, Russell W., and Heinke, Harry S., Jr.: Investigation of the Damping in Roll of Swept and Tapered Wings at Supersonic Speeds. NACA RM L53A13, 1953.
83. Chubb, Robert S.: Experimental Investigation of the Static Aerodynamic and Dynamic Damping-in-Roll Characteristics of an 8-CM Aircraft Rocket With Solid and Slotted Fins. NACA RM A52C04, 1952.
84. Spearman, M. Leroy, and Hilton, John H., Jr.: Aerodynamic Characteristics at Supersonic Speeds of a Series of Wing-Body Combinations Having Cambered Wings With an Aspect Ratio of 3.5 and a Taper Ratio of 0.2. Effects of Sweep Angle and Thickness Ratio on the Static Lateral Stability Characteristics at  $M = 1.60$ . NACA RM L51K15a, 1952.
85. Hamilton, Clyde V.: Aerodynamic Characteristics at Supersonic Speeds of a Series of Wing-Body Combinations Having Cambered Wings With an Aspect Ratio of 3.5 and a Taper Ratio of 0.2. Effects of Sweep Angle and Thickness Ratio on the Static Lateral Stability Characteristics at  $M = 2.01$ . NACA RM L52E23, 1952.
86. Lessing, Henry C.: Aerodynamic Study of a Wing-Fuselage Combination Employing a Wing Swept Back 63° - Effect of Sideslip on Aerodynamic Characteristics at a Mach Number of 1.4 With the Wing Twisted and Cambered. NACA RM A50F09, 1950.
87. Scherrer, Richard, and Dennis, David H.: Lateral-Control Characteristics and Dihedral Effect of a Wing-Body Combination With a Variable-Incidence Triangular Wing and Wing-Tip Ailerons at a Mach Number of 1.52. NACA RM A50H10, 1951.

## Complete Model Configurations

88. Campbell, John P., and Toll, Thomas A.: Factors Affecting Lateral Stability and Controllability. NACA RM L8A28a, 1948.
89. Fisher, Lewis R., and Michael, William H., Jr.: An Investigation of the Effect of Vertical-Fin Location and Area on Low-Speed Lateral Stability Derivatives of a Semitailless Airplane Model. NACA RM L51A10, 1951.
90. Letko, William, and Riley, Donald R.: Effect of an Unswept Wing on the Contribution of Unswept-Tail Configurations to the Low-Speed Static- and Rolling-Stability Derivatives of a Midwing Airplane Model. NACA TN 2175, 1950.
91. Goodman, Alex: Effects of Wing Position and Horizontal-Tail Position on the Static Stability Characteristics of Models With Unswept and 45° Sweptback Surfaces With Some Reference to Mutual Interference. NACA TN 2504, 1951.
92. Bird, John D., Lichtenstein, Jacob H., and Jaquet, Byron M.: Investigation of the Influence of Fuselage and Tail Surfaces on Low-Speed Static Stability and Rolling Characteristics of a Swept-Wing Model. NACA TN 2741, 1952. (Supersedes NACA RM L7H15.)
93. Letko, William: Effect of Vertical-Tail Area and Length on the Yawing Stability Characteristics of a Model Having a 45° Sweptback Wing. NACA TN 2358, 1951.
94. Bird, John D., Jaquet, Byron M., and Cowan, John W.: Effect of Fuselage and Tail Surfaces on Low-Speed Yawing Characteristics of a Swept-Wing Model As Determined in Curved-Flow Test Section of the Langley Stability Tunnel. NACA TN 2483, 1951. (Supersedes NACA RM L8G13.)
95. Goodman, Alex, and Wolhart, Walter D.: Experimental Investigation of the Low-Speed Static and Yawing Stability Characteristics of a 45° Sweptback High-Wing Configuration With Various Twin Vertical Wing Fins. NACA TN 2534, 1951.
96. Jaquet, Byron M., and Brewer, Jack D.: Effects of Various Outboard and Central Fins on Low-Speed Static-Stability and Rolling Characteristics of a Triangular-Wing Model. NACA RM L9E18, 1949.
97. Goodman, Alex: Effect of Various Outboard and Central Fins on Low-Speed Yawing Stability Derivatives of a 60° Delta-Wing Model. NACA RM L50E12a, 1950.

98. Bird, John D., Fisher, Lewis R., and Hubbard, Sadie M.: Some Effects of Frequency on the Contribution of a Vertical Tail to the Free Aerodynamic Damping of a Model Oscillating in Yaw. NACA TN 2657, 1952.
99. Fisher, Lewis R., and Wolhart, Walter D.: Some Effects of Amplitude and Frequency on the Aerodynamic Damping of a Model Oscillating Continuously in Yaw. NACA TN 2766, 1952.
100. Wolhart, Walter D.: Influence of Wing and Fuselage on the Vertical-Tail Contribution to the Low-Speed Rolling Derivatives of Midwing Airplane Models With  $45^\circ$  Sweptback Surfaces. NACA TN 2587, 1951.
101. Letko, William: A Low-Speed Experimental Study of the Directional Characteristics of a Sharp-Nosed Fuselage Through a Large Angle-of-Attack Range at Zero Angle of Sideslip. NACA TN 2911, 1953.
102. Jaquet, Byron M., and Fletcher, H. S.: Lateral Oscillatory Characteristics of the Republic F-91 Airplane Calculated by Using Low-Speed Experimental Static and Rotary Derivatives. NACA RM L53G01, 1953.
103. Queijo, M. J., and Wells, Evalyn G.: Wind-Tunnel Investigation of the Low-Speed Static and Rotary Stability Derivatives of a 0.13-Scale Model of the Douglas D-558-II Airplane in the Landing Configuration. NACA RM L52G07, 1952.
104. Johnson, Joseph L.: Damping in Yaw and Static Directional Stability of a Canard Airplane Model and of Several Models Having Fuselages of Relatively Flat Cross Section. NACA RM L50H30a, 1950.
105. Bates, William R.: Low-Speed Static Lateral Stability Characteristics of a Canard Model Having a  $60^\circ$  Triangular Wing and Horizontal Tail. NACA RM L9J12, 1949.
106. Delany, Noel K., and Hayter, Nora-Lee F.: Low-Speed Investigation of a 0.16-Scale Model of the X-3 Airplane - Lateral and Directional Characteristics. NACA RM A51A16, 1951.
107. Rose, Leonard M.: Low-Speed Investigation of a Small Triangular Wing of Aspect Ratio 2.0. III - Static Stability With Twin Vertical Fins. NACA RM A8C03, 1948.
108. McCormack, Gerald M.: Aerodynamic Study of a Wing-Fuselage Combination Employing a Wing Swept Back  $63^\circ$ . Aerodynamic Characteristics in Sideslip of a Large-Scale Model Having a  $63^\circ$  Swept-Back Vertical Tail. NACA RM A9F14, 1949.

109. Anderson, Adrien E.: An Investigation at Low Speed of a Large-Scale Triangular Wing of Aspect Ratio Two. III. Characteristics of Wing With Body and Vertical Tail. NACA RM A9H04, 1949.
110. Koenig, David G.: Tests in the Ames 40- by 80-Foot Wind Tunnel of an Airplane Configuration With a Variable-Incidence Triangular Wing and an All-Movable Horizontal Tail. NACA RM A53D21, 1953.
111. Koenig, David G.: Tests in the Ames 40- by 80-Foot Wind Tunnel of an Airplane Configuration With an Aspect Ratio 3 Triangular Wing and an All-Movable Horizontal Tail - Longitudinal and Lateral Characteristics. NACA RM A52L15, 1953.
112. Graham, David, and Koenig, David G.: Tests in the Ames 40- by 80-Foot Wind Tunnel of an Airplane Configuration With an Aspect Ratio 2 Triangular Wing and an All-Movable Horizontal Tail - Lateral Characteristics. NACA RM A51L03, 1952.
113. Marino, Alfred A., and Mastrocola, N.: Wind-Tunnel Investigation of the Contribution of a Vertical Tail to the Directional Stability of a Fighter-Type Airplane. NACA TN 2488, 1952. (Supersedes NACA RM L7K03.)
114. Falkner, V. M., and Nixon, H. L.: Wind Tunnel Tests on the Yawing Moment of a Meteor Model. Rep. No. 11,943, British A.R.C., Nov. 25, 1948.
115. Ross, J. G., and Lock, R. C.: Wind-Tunnel Measurements of Yawing Moment Due to Yawing ( $n_r$ ) on a 1/5.5 Scale Model of the Meteor Mark F.III. R. & M. No. 2791, British A.R.C., 1947.
116. Spearman, M. Leroy, and Becht, Robert E.: The Effect of Negative Dihedral, Tip Droop, and Wing Tip Shape on the Low-Speed Aerodynamic Characteristics of a Complete Model Having a 45° Sweptback Wing. NACA RM L8J07, 1948.
117. Goodson, Kenneth W., and Few, Albert G., Jr.: Low-Speed Static Longitudinal and Lateral Stability Characteristics of a Model With Leading-Edge Chord-Extensions Incorporated on a 40° Sweptback Circular-Arc Wing of Aspect Ratio 4 and Taper Ratio 0.50. NACA RM L52L18, 1952.
118. Schuldenfrei, Marvin, Comisarow, Paul, and Goodson, Kenneth W.: Stability and Control Characteristics of a Complete Airplane Model Having a Wing With Quarter-Chord Line Swept Back 40°, Aspect Ratio 2.50, and Taper Ratio 0.42. NACA TN 2482, 1951. (Supersedes NACA RM L7B25.)
119. Goodson, Kenneth W., and Comisarow, Paul: Lateral Stability and Control Characteristics of an Airplane Model Having a 42.8° Sweptback Circular-Arc Wing With Aspect Ratio 4.00, Taper Ratio 0.50, and Sweptback Tail Surfaces. NACA RM L7G31, 1947.

120. Polhamus, Edward C.: Wind-Tunnel Investigation of the Low-Speed Stability and Control Characteristics of a Model With a Sweptback Vee Tail and a Sweptback Wing. NACA RM L7K13, 1948.
121. Kemp, William B., Jr., and Becht, Robert E.: Stability and Control Characteristics at Low Speed of a 1/4-Scale Bell X-5 Airplane Model. Lateral and Directional Stability and Control. NACA RM L50C17a, 1950.
122. Polhamus, Edward C., and Becht, Robert E.: Low-Speed Stability Characteristics of a Complete Model With a Wing of W Plan Form. NACA RM L52A25, 1952.
123. Kuhn, Richard E., and Wiggins, James W.: Static Lateral Stability Characteristics of a 1/10-Scale Model of the X-1 Airplane at High Subsonic Mach Numbers. NACA RM L51F01a, 1951.
124. Donlan, Charles J., and Kuhn, Richard E.: Estimated Transonic Flying Qualities of a Tailless Airplane Based on a Model Investigation. NACA RM L9D08, 1949.
125. Wiggins, James W., Kuhn, Richard E., and Fournier, Paul G.: Wind-Tunnel Investigation To Determine the Horizontal- and Vertical-Tail Contributions to the Static Lateral Stability Characteristics of a Complete-Model Configuration at High Subsonic Speeds. NACA RM L53E19, 1953.
126. Kuhn, Richard E., and Wiggins, James W.: Wind-Tunnel Investigation To Determine the Aerodynamic Characteristics in Steady Roll of a Model at High Subsonic Speeds. NACA RM L52K24, 1953.
127. Purser, Paul E., and Mitchell, Jesse L.: Miscellaneous Directional-Stability Data for Several Airplane-Like Configurations From Rocket-Model Tests at Transonic Speeds. NACA RM L52E06b, 1952.
128. White, Maurice D.: Effect of Camber and Twist on the Stability Characteristics of Models Having a 45° Swept Wing As Determined by the Free-Fall Method at Transonic Speeds. NACA RM A52F16, 1952.
129. Gillis, Clarence L., and Mitchell, Jesse L.: Flight Tests at Transonic and Supersonic Speeds of an Airplane-Like Configuration With Thin Straight Sharp-Edge Wings and Tail Surfaces. NACA RM L8K04a, 1949.
130. D'Aiutolo, Charles T., and Mason, Homer P.: Preliminary Results of the Flight Investigation Between Mach Numbers of 0.80 and 1.36 of a Rocket-Powered Model of a Supersonic Airplane Configuration Having a Tapered Wing With Circular-Arc Sections and 40° Sweepback. NACA RM L50H29a, 1950.

131. D'Aiutolo, Charles T., and Parker, Robert N.: Preliminary Investigation of the Low-Amplitude Damping in Pitch of Tailless Delta- and Swept-Wing Configurations at Mach Numbers From 0.7 to 1.35. NACA RM L52G09, 1952.
132. Spearman, M. Leroy, and Robinson, Ross B.: The Aerodynamic Characteristics of a Supersonic Aircraft Configuration With a 40° Sweptback Wing Through a Mach Number Range From 0 to 2.4 As Obtained From Various Sources. NACA RM L52A21, 1952.
133. Spearman, M. Leroy: An Investigation of a Supersonic Aircraft Configuration Having a Tapered Wing With Circular-Arc Sections and 40° Sweepback. Static Lateral Stability Characteristics at Mach Numbers of 1.40 and 1.59. NACA RM L50C17, 1950.
134. Sherrer, Richard, and Dennis, David H.: Damping in Roll of a Missile Configuration With a Modified Triangular Wing and a Cruciform Tail at a Mach Number of 1.52. NACA RM A51A03, 1951.
135. Phelps, E. Ray, and Lazzeroni, Frank A.: Wind-Tunnel Investigation of the Aerodynamic Characteristics of 1/15-Scale Model of the Northrop MX-775A Missile. NACA RM A51E28, 1951.
136. Blalock, James E., and Broberg, Ralph F.: Wind-Tunnel Tests of a 1/3-Scale Model of the Turbojet Version XSUM-N-2 (Grebe) Pilotless Aircraft. Part I - Lateral Stability and Control Characteristics. Rep. C-156 Aero 759, David Taylor Model Basin, Navy Dept., Oct. 1948.
137. Spahr, J. Richard, and Robinson, Robert A.: Wind-Tunnel Investigation at Mach Numbers of 1.5 and 2.0 of a Canard Missile Configuration. NACA RM A51C08, 1951.
138. Darling, J. A., and DeMeritte, F. J.: Static Stability Measurements on 1/17th Scale Modified Shrike at Mach Number 1.87. NAVORD Rep. 2364 (Aeroballistic Res. Rep. 87), U. S. Naval Ord. Lab. (White Oak, Md.), June 10, 1952.
139. Turner, Robert L., and Lobrecht, Dorr, Jr.: Stability and Control Tests of a 0.135-Scale Sperry XAAM-N-2 Model at Mach Number 2.00. OAL Rep. 112-15, Ord. Aerophysics Lab. (Daingerfield, Tex.), May 12, 1951.
140. Darling, J. A., and DeMeritte, F. J.: Static Stability Measurements on Rascal Missile (MX-776) at Mach Number 1.56. NAVORD Rep. 2362 (Aeroballistic Res. Rep. 85), U. S. Naval Ord. Lab. (White Oak, Md.), June 11, 1952.

141. Clancy, Thomas M.: Wind-Tunnel Investigation of the RS-9 Meteor at Mach Numbers 1.56, 1.87, 2.16, 2.48, and 2.87. NAVORD Rep. 2414 (Aeroballistic Res. Rep. 94), U. S. Naval Ord. Lab. (White Oak, Md.), July 17, 1952.
142. Anderson, Arnold W., and Putnam, Russell H.: Wind-Tunnel Tests of a 0.65-Scale Model XKD5G-1 Pilotless Target Aircraft. Part III - Lateral and Directional Stability and Control Characteristics. Rep. C-413 Aero 799, The David W. Taylor Model Basin, Navy Dept., Mar. 1951.
143. Turner, Robert L., Jr., and Jackson, C. E.: Stability and Control Tests of a 0.135-Scale Sperry XAAM-N-2 Model at Mach Number 1.50. OAL Rep. 112-16, Ord. Aerophysics Lab. (Daingerfield, Tex.), June 22, 1951.
144. Turner, Robert L., Jr., and Jackson, C. E.: Stability and Control Tests of a 0.135-Scale Sperry XAAM-N-2 Model at Mach Number 2.50. OAL Rep. 112-17 (Contract NOrd-9028, Bur. Ord.), Ord. Aerophysics Lab. (Daingerfield, Tex.), June 25, 1951.
145. Spearman, M. Leroy, and Robinson, Ross B.: Wind-Tunnel Investigation of a Ram-Jet Canard Missile Model Having a Wing and Canard Surfaces of Delta Plan Form With 70° Swept Leading Edges. Longitudinal and Lateral Stability and Control Characteristics at a Mach Number of 1.60. NACA RM L52E15, 1952.
146. Hamilton, Clyde V., Driver, Cornelius, and Sevier, John R., Jr.: Wind-Tunnel Investigation of a Ram-Jet Missile Model Having a Wing and Canard Surfaces of Delta Plan Form With 70° Swept Leading Edges. Force and Moment Characteristics of Various Combinations of Components at a Mach Number of 1.6. NACA RM L53A14, 1953.
147. Watts, P. E.: Preliminary Force and Moment Measurements on a Cruciform Rectangular Wing-Body Combination at Mach Number 1.57. Tech. Memo. No. Aero 285, British R.A.E., June 1952.
148. Krieger, Robert H.: Supersonic Wind Tunnel Tests of a Model of the North American Guided Missile MX 770 at Mach No. 172. Memo. Rep. No. 566, Ballistic Res. Labs., Aberdeen Proving Ground, Sept. 1951.
149. Beal, R. R.: Roll-Damping and Additional Roll-Control Characteristics of the Sparrow 14-B at  $M = 2.50$  As Determined by Wind-Tunnel Tests of a 13.5-Percent-Scale Model. Rep. No. SM-14062 (Contract NOa(s)-51-513, Bur. Aero.), Douglas Aircraft Co., Inc., Dec. 18, 1951.

## THREE HIGH-SPEED MODELS




Figure 1


EFFECTIVE-DIHEDRAL DERIVATIVE  $C_{l\beta}$   
FOR THREE HIGH-SPEED MODELS

Figure 2

DIRECTIONAL-STABILITY DERIVATIVE  $C_{n\beta}$   
FOR THREE HIGH-SPEED MODELS




Figure 3

VARIATION OF DIRECTIONAL-STABILITY DERIVATIVE  $C_{n\beta}$   
WITH HORIZONTAL-TAIL HEIGHT




Figure 4

VARIATION OF EFFECTIVE-DIHEDRAL DERIVATIVE  $C_{l\beta}$   
WITH HORIZONTAL-TAIL HEIGHT




Figure 5

EFFECT OF CHORD-EXTENSIONS ON CHARACTERISTICS OF  
MODEL III




Figure 6

VARIATION OF THE DAMPING IN ROLL  $C_{lp}$  WITH MACH NUMBER AND ANGLE OF ATTACK




Figure 7

VARIATION OF THE DAMPING IN ROLL  $C_{lp}$  WITH ANGLE OF ATTACK  
 $M = 0.85$




Figure 8

TYPICAL VARIATIONS OF THE ROLLING-MOMENT  
COEFFICIENT  $C_l$  WITH RATE OF ROLL  $\frac{pb}{2V}$




Figure 9

EFFECT OF FENCE ON CHARACTERISTICS  
OF A 45° SWEEP WING




Figure 10

$C_{l\beta}$  DERIVATIVE FOR THREE HIGH-SPEED MODELS




Figure 11

$C_{n\beta}$  DERIVATIVE FOR THREE HIGH-SPEED MODELS




Figure 12

SECURITY INFORMATION

NASA Technical Library



3 1176 01438 0159

